according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020

Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 1 z 9

Trade Name: SILVER WEBS

# SECTION 1: Identification of the mixture and the company/undertaking

#### 1.1 Product identifier:

| Trade Name:          | SILVER WEBS                |
|----------------------|----------------------------|
| Mixture description: | Solvent coating (aerosol). |
| UFI codes:           | G8DM-905C-W00C-73Q9        |

#### 1.2 Relevant identified uses of the mixture or mixture and uses advised against:

Identified uses: Paint, surface treatment. Recommended for identified uses. Uses advised against:

# 1.3 Details of the supplier of the safety data sheet:

# **GOX7-EUROPE** s.r.o.

Chlumčanská 396 439 02 Cítoliby Czech Republic Tel.: +420 777 691 661

competent person responsible for MSDS: info@gox7.cz

# 1.4 Emergency telephone number:

112 (General emergency phone).

## **SECTION 2: Hazards identification**

The mixture is classified as dangerous as follows:

#### 2.1 Classification of the mixture:

Aerosol 1; H222, H229 according to 1272/2008/EC **Eye Irrit. 2; H319 STOT SE 3; H336** 

Full text of H-phrases: see section 16.

## The most important adverse physicochemical, human health and environmental effects:

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

#### 2.2 Label elements:

| hazard pictograms                           |  |  |  |  |  |  |  |  |
|---|--|--|--|--|--|--|--|--|
| signal word                                 | Danger.  |  |  |  |  |  |  |  |
| ingredients of the mixture to be<br>labeled | Contains acetone, 2-butanone, <i>n</i> -butyl-acetate.   |  |  |  |  |  |  |  |
| hazard statements                           | <ul> <li>H222 Extremely flammable aerosol.</li> <li>H229 Pressurised container: May burst if heated.</li> <li>H319 Causes serious eye irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> </ul>  |  |  |  |  |  |  |  |
| precautionary statements                    | <ul> <li>P102 Keep out of reach of children.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P403 Store in a well-ventilated place.</li> <li>P211 Do not spray on an open flame or other ignition source.</li> </ul> |  |  |  |  |  |  |  |

P251 Do not pierce or burn, even after use.

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020

Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 2 z 9

Trade Name: SILVER WEBS

|                                 | P280 Wear protective gloves/protective clothing/eye protection.                              |
|---------------------------------|--|
|                                 | P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.              |
|                                 | P501 Dispose of contents/container at the site of hazardous waste collection in the village. |
|                                 | EUH066 Repeated exposure may cause skin dryness or cracking.                                 |
| supplemental hazard information | EUH208 Contains (di-n-butyltin)-dilaurate. May produce an allergic reaction.                 |
|                                 | VOC: 79%   |

#### 2.3 Other hazards:

The mixture meets not the criteria for PBT or vPvB.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

# 3.2.1 Substances presenting a health or environmental hazard in the mixture

| Chemical identity                      | CAS        | EC-No.<br>Registration No.             | Content **)<br>(wt. %) | Classification<br>1272/2008/EC  |
|--|------------|--|------------------------|---|
| 2-butanone; ethyl methyl<br>ketone     | 78-93-3    | 201-159-0<br>not available             | approx. 42             | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>EUH066   |
| petroleum gases,<br>liquefied (LPG) *) | 68476-85-7 | 270-704-2<br>not available             | approx. 25             | Flam. Gas 1; H220<br>Press. Gas (Liq.); H280  |
| acetone                                | 67-64-1    | 200-662-2<br>01-2119471330-<br>49-0102 | approx. 13             | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>EUH066   |
| <i>n</i> -butyl-acetate                | 123-86-4   | 204-658-1<br>not available             | < 4                    | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>EUH066   |
| aluminium powder<br>(stabilised)       | 7429-90-5  | 231-072-3<br>not available             | < 3                    | Flam. Sol. 1; H228<br>Water-react. 2; H261  |
| (di-n-butyltin) - dilaurate            | 77-58-7    | 201-039-8<br>not available             | < 0,21                 | Acute Tox. 4; H302 Repr 1B; H360FD Muta. 2; H341 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens 1; H317 STOT RE 1; H372 STOT SE 1; H370 Aquatic Acute 1; H400, M=1 Aquatic Chronic 1; H410, M=1 |

<sup>\*)</sup> Contains less than 0.1% of 1,3-butadiene; \*\*) see section 16 classification procedure.

## 3.2.2 Impurities, stabilising aditives, constituents other than the main constituent

| I |          | · · · · · · · · · · · · · · · · · · · |   | ······ |                            |                        |                                |
|---|----------|---------------------------------------|---|--------|----------------------------|------------------------|--------------------------------|
|   | Chemical | identity                              | C | AS     | EC-No.<br>Registration No. | Content **)<br>(wt. %) | Classification<br>1272/2008/EC |
|   | not ider | ntified                               | - |        |                            |                        |                                |
|   |          |                                       |   |        |                            |                        |                                |

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18, 10, 2020

Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 3 z 9

Trade Name: SILVER WEBS

## **SECTION 4: First aid measures**

Keep the person at physical and mental rest and warm. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

#### 4.1 Description of first aid measures:

#### Inhalation:

Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. Place unconscious person on the side in the recovery position and ensure breathing can take place.

#### Skin contact:

Remove contaminated clothing immediately and wash skin with soap and water. Do not use solvents or thinners.

#### Eye contact:

Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes (least 15 minutes). Get medical attention.

#### Ingestion:

Unlikely (aerosol). If this nevertheless happens, rinse out mouth with clean water. Do not induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

## 4.2 Most important symptoms and effects, both acute and delayed:

Overexposure may result in light headedness, staggering gait, dizziness, and possible nausea. May cause severe eye irritation. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness and possible contact dermatitis. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane irritation and adverse effects on the kidneys, liver and central nervous system. May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Treat symptomatically and supportively.

#### SECTION 5: Firefighting measures

# 5.1 Extinguishing media:

#### Suitable extinguishing media:

Use water fog, dry chemical, carbon dioxide or foam.

#### Extinguishing media which shall not be used for safety reasons:

Solid streams of water may be ineffective. Burning product will float on the surface and spread fire.

#### 5.2 Special hazards arising from the substance:

Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapours are heavier than air and may travel along surfaces to remote ignition sources and flash back. Combustion will produce oxides of carbon and hydrocarbons.

#### 5.3 Advice for fire-fighters:

In the event of fire, wear self-contained breathing apparatus and clothing protective against chemicals. Keep extinguishing aerosols away from the danger area, if possible without risk.

# SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Use non-sparking tools, avoid electrostatic charge. Other protective measures - see section 7.

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020 Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 4 z 9

Trade Name: SILVER WEBS

#### 6.2 Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Do not allow to enter waters or soil. Report spills to authorities as required.

## 6.3 Methods and material for containment and cleaning up:

Aerosol, mainly local air pollution will occur. If, however, a liquid fraction is leaking, absorb spillage using an absorbent, such as earth, sand or vermiculite. Place in container for disposal according to local regulations (see section 13). Pump off larger quantities. Use non-sparking tools.

Afterwards ventilate area and wash spill site.

#### 6.4 Reference to other sections:

Protective equipment: see section 8. Dispose according to the section 13.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling:

Provision of very good ventilation in the working area. Vapour/air mixtures are heavier than air. Adequate ventilation at the floor area must be ensured as well. Eye bath required. These locations must be signposted clearly. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. Keep containers tightly sealed. Prevent formation of aerosols. Do not use any tools that cause sparks.

When using, do not eat, drink or smoke. Wash hands with warm water and soap before breaks and after work.

#### 7.2 Conditions for safe storage, including any incompatibilities:

Store in original tightly closed packing in dry and well-ventilated areas. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature: 5 - 30 °C. Keep away from direct sunlight.

#### 7.3 Specific end use(s):

In household and industry.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

## 8.1.1 Exposure limit value in UK:

LPG: acetone:

8 h: 1750 mg/m<sup>3</sup> short: 2180 mg/m<sup>3</sup> 8 h: 1210 mg/m<sup>3</sup> short: 3620 mg/m<sup>3</sup>

<u>n-butyl-acetate:</u> <u>2-butanon:</u>

8 h: 724 mg/m<sup>3</sup>, short: 966 mg/m<sup>3</sup> 8 h: 600 mg/m<sup>3</sup> short: 899 mg/m<sup>3</sup>

#### 8.1.2 DNEL/PNEC: for acetone

DNEL (oral, long-term, general population): 62 mg/kg (body weight/day, systemic effect)

DNEL (dermal, long-term, general population): 62 mg/kg (body weight/day, systemic effect)

DNEL (dermal, long-term, workers): 186 mg/kg (body weight/day, systemic effect)

DNEL (inhalation, long-term, workers): 1210 mg/m³ (systemic effect)

DNEL (inhalation, acute, workers): 2420 mg/m³ (local effect)

DNEL (inhalation, long-term, general population): 200 mg/m3 (systemic effect)

PNEC fresh water 10,6 mg/l
PNEC seawater 3,04 mg/l
PNEC fresh water sediment 30,4 mg/kg
PNEC sediment sea 0,142 mg/kg
PNEC intermittent discharge 21 mg/l
PNEC soil 29.5 mg/kg
PNEC STP 100 mg/l

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020 Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 5 z 9

Trade Name: SILVER WEBS

#### 8.2 Exposure controls

## 8.2.1 Exposure reduction (technical measures):

Where exposure cannot be prevented by other means the use of individual protection measures, such as personal protection equipment is necessary. Ensure adequate ventilation of the workplace. Regularly measure the concentration of this agent in the workplace atmosphere.

## 8.2.2 Individual protection measures, such as personal protective equipment:

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier. Workers in the risky process/areas identified should be trained.

| Respiratory protection: | Required when vapours/aerosols are generated (recommended filter type A) and where risk assessment shows air-purifying respirators are appropriate use. |
|-------------------------|---|
| Hand protection:        | Handle with gloves, e.g. nitril-rubber, strength > 0.55 mm, penetration time > 480 min.; leather is not suitable.                                       |
| Eye/face protection:    | chemical safety goggles   |
| Skin protection:        | suitable protective clothing  |

## 8.2.3 Environmental exposure reduction:

Uncontrolled escape of substance/formulation into environment is to be avoided.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties:

| <b>Appearance</b> (at 20 °C             | C):                | aerosol                                |  |  |  |  |  |  |  |
|---|--------------------|--|--|--|--|--|--|--|--|
| Colour:                                 |                    | depending on the colour of the pigment |  |  |  |  |  |  |  |
| Odour:                                  |                    | characteristic                         |  |  |  |  |  |  |  |
| Odour threshold:                        |                    | not available                          |  |  |  |  |  |  |  |
| <b>pH</b> (at 20 °C):                   |                    | 6; 10%                                 |  |  |  |  |  |  |  |
| Melting point/freezir                   | ng point:          | not available                          |  |  |  |  |  |  |  |
| <b>Boiling point</b> (range)            | ) <b>:</b>         | not available                          |  |  |  |  |  |  |  |
| Flash point:                            |                    | < -18 °C (propellant gas)              |  |  |  |  |  |  |  |
| Evaporation rate:                       |                    | not available                          |  |  |  |  |  |  |  |
| Flammability:                           |                    | flammable mixture                      |  |  |  |  |  |  |  |
| Evalosivo limito                        | lower: (% vol.)    | 1,8 (propellant gas)                   |  |  |  |  |  |  |  |
| Explosive limits                        | upper: (% vol.)    | 12,8 (propellant gas)                  |  |  |  |  |  |  |  |
| Vapour pressure: (2                     | 0 °C)              | not available                          |  |  |  |  |  |  |  |
| Vapour density:                         |                    | not available                          |  |  |  |  |  |  |  |
| Relative density:                       |                    | not available                          |  |  |  |  |  |  |  |
| Solubility in water (                   | 20 °C) :           | not available                          |  |  |  |  |  |  |  |
| Partition coefficient                   | : n-octanol/water: | not available                          |  |  |  |  |  |  |  |
| Auto-ignition tempe                     | rature:            | not available                          |  |  |  |  |  |  |  |
| Decomposition temp                      | perature:          | not available                          |  |  |  |  |  |  |  |
| Viscosity:                              |                    | not available                          |  |  |  |  |  |  |  |
| Particle characterist                   | tics:              | not available                          |  |  |  |  |  |  |  |
| 9.2 Other informatior                   | 1                  |  |  |  |  |  |  |  |  |
| Information with reg<br>hazard classes: | ard to physical    | not available                          |  |  |  |  |  |  |  |
| Evaporation rate:                       |                    | not available                          |  |  |  |  |  |  |  |

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020 Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 6 z 9

Trade Name: SILVER WEBS

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity:

Low reactivity.

#### 10.2 Chemical stability:

Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions:

Not known.

#### 10.4 Conditions to avoid:

Heat, flames and sparks. Protect from higher temperatures (over 50 ° C) and direct sunlight, risk of aerosol packaging explosion. Do not use in the presence of a source of ignition.

# 10.5 Incompatible materials:

Strong oxidizing agents.

# 10.6 Hazardous decomposition products:

Carbon oxides.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

Acute toxicity:

| Acute toxicity:  |   |
|--|---|
| - LD <sub>50</sub> oral, rat (mg.kg <sup>-1</sup> ):               | ATE mixture > 2000 (ATE components used according to CLP Table 3.1.2, as the laboratory data obtained do not correspond to the harmonized classification) |
| - LD <sub>50</sub> skin, rat or rabbit (mg.kg <sup>-1</sup> ):     | does not contain components with this classification  |
| - LC <sub>50</sub> inhalation, rat, gas or vapour (mg. $l^{-1}$ ): | does not contain components with this classification  |
| Skin corrosion/irritation:   | does not reach the limit for classification   |
| Serious eye damage/irritation:                                     | irritant, cat. 2  |
| Respiratory or skin sensitisation:                                 | does not reach the limit for classification   |
| Germ cell mutagenicity:  | no  |
| Carcinogenicity:   | no  |
| Reproductive toxicity:   | no  |
| STOT-single exposure:  | may cause drowsiness or dizziness   |
| STOT-repeated exposure:  | may cause skin dryness and cracking   |
| Aspiration hazard:   | no  |
| 11.2 Information on other hazards:                                 |   |
|  |   |

**Endocrine disrupting properties:** does not contain these substances

Additional information:

not known

# SECTION 12: Ecological information

|  | ı | 4 | į | • |   | ĺ | ı | L |  | ı | ı | ( | ĺ | J | ) | ١ | ĺ | ĺ | Į | ĺ | ; | ı | l |   | ١ | / | • |   |
|--|---|---|---|---|---|---|---|---|--|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  |   |   |   |   | ٠ | ٠ |   |   |  | ٠ |   | ٠ |   |   |   |   |   |   |   |   |   |   |   | ٠ | ť |   |   | , |

| l ————————————————————————————————————               |   |
|--|---|
| - LC <sub>50</sub> 96 H, fish (mg.l <sup>-1</sup> ): | no data available                             |
| - EC₅₀ 24 H, Daphnia (mg.l⁻¹):                       | no data available                             |
| - IC₅₀ 72 H, algae (mg.l⁻¹):                         | no data available                             |
| 12.2 Persistence and degradability:                  | no data available                             |
| 12.3 Bioaccumulative potential:                      | no data available                             |
| 12.4 Mobility in soil:                               | no data available                             |
| 12.5 Results of PBT and vPvB assessment:             | product is neither a PBT nor a vPvB substance |

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020 Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 7 z 9

Trade Name: SILVER WEBS

**12.6 Endocrine disrupting properties:** does not contain these substances

12.70ther adverse effects:

Classification according to additional method of CLP.

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods:

#### Disposal methods of the substance and the contaminated packaging:

Fully use the aerosol. Do not take the unused product into the collection or other disposal. Do not throw into the fire! Dispose of the packaging after full emptying. Never remove it by draining into drains! The waste producer is responsible for sorting waste and disposing of. Potential EU waste-code 08 01 11 for container, 15 01 10 for mixture.

### Physical/chemical properties that may affect waste treatment options:

Extremely flammable.

#### Union provisions relating to waste:

- directive 2008/98/EC

# **SECTION 14: Transport Information**

| OLOTION 14. Transport information                             |                     |  |  |  |  |  |  |  |  |
|---|---------------------|--|--|--|--|--|--|--|--|
| 14.1 UN number:   | 1950                |  |  |  |  |  |  |  |  |
| 14.2 UN proper shipping name:                                 |                     |  |  |  |  |  |  |  |  |
| - ADR/RID/IMDG/IATA   | AEROSOLS, flammable |  |  |  |  |  |  |  |  |
| 14.3 Transport hazard class(es):                              | 2                   |  |  |  |  |  |  |  |  |
| 14.4 Packing group:   | -                   |  |  |  |  |  |  |  |  |
| 14.5 Environmental hazards:                                   | no                  |  |  |  |  |  |  |  |  |
| 14.6 Special precautions for user:                            | none                |  |  |  |  |  |  |  |  |
| 14.7 Maritime transport in bulk according to IMO instruments: | not available       |  |  |  |  |  |  |  |  |
| ADR/RID:  |                     |  |  |  |  |  |  |  |  |
| - classification code   | 5F                  |  |  |  |  |  |  |  |  |
| - labels  | 2.1                 |  |  |  |  |  |  |  |  |
| - hazard identification code                                  | -                   |  |  |  |  |  |  |  |  |
| - tunnel restriction code                                     | D                   |  |  |  |  |  |  |  |  |
| IMDG:   |                     |  |  |  |  |  |  |  |  |
| - EmS   | F-D, S-U            |  |  |  |  |  |  |  |  |

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the mixture:

Regulation No. 1907/2006/ES, REACH. Regulation No. 1272/2008/ES, CLP.

#### 15.2 Chemical safety assessment:

No data available.

#### SECTION 16: Other information

#### Reason for alteration:

23. 03. 2022 - Classification changes of mixture components, changes in Sections 9, 11 and 12.

#### Key or legend to abbreviations and acronyms used in the safety data sheet:

Flam Gas 1 flammable gas, cat. 1

Press. Gas (liq.) gas under pressure (liquefied)
Flam. Liq. 3 flammable liquid, cat. 3
Flam. Liq. 2 flammable liquid, cat. 2
Aerosol 1 highly flammable aerosol

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020 Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 8 z 9

Trade Name: SILVER WEBS

STOT SE 3 specific target organ toxicity after single exposure, cat. 3
Aquatic Acute 1 hazardous to the aquatic environment, acute, cat. 1
Aquatic Chronic 1 hazardous to the aquatic environment, long term, cat. 1

Repr. 1B reproduction toxicity, cat. 1B

Muta. 2 mutagenicity, kat. 2 Skin Corr. 1C corrosion, kat. 1C

Skin Sens. 1 sensitisation for skin, kat. 1
Skin Irrit. 2 irritating for skin, cat. 2
Eye Irrit. 2 irritating for eyes, cat. 2
Acute Tox. 4 acute toxicity, cat. 4

STOT RE 1 specific target organ toxicity after repeated exposure, cat. 1
STOT SE 1 specific target organ toxicity after single exposure, cat. 1

Eye Dam. 1 eye damage, cat. 1
Water-react. 2 react with water, kat. 2
Flam. Sol. 1 flammable solid, kat. 1

NOEC No Observed Effect Concentration

PBT Persistent, bioaccumulative, toxic chemical

vPvB Very Persistent and Very Bioaccumulative chemical

DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration
CLP regulation No. 1272/2008/EC
REACH regulation No. 1907/2006/EC

bw body weight

#### Sources of key data used to compile the Safety Data Sheet:

Chemical databases and tables, tests.

# List of H-phrases:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H226 Flammable liquid and vapour. H225 Highly flammable liquid and vapour.

H220 Extremely flammable gas.

H228 Flammable solid.

H261 In contact with water releases flammable gases.
H360FD May damage fertility. May damage the unborn child.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
 H341 Suspected of causing genetic defects
 H336 May cause drowsiness or dizziness.

H410 very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic lifeH315 Causes skin irritation.

H319 Causes serious eye irritation.

H302 Harmful if swallowed

H318 Causes serious eye damage. H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 18. 10. 2020 Product code: GM7003

Revision: 23. 03. 2022 Replaced version: 18. 10. 2020 Page: 9 z 9

Trade Name: SILVER WEBS

P403 Store in a well-ventilated place.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container at the site of hazardous waste collection in the

village.

# Training advice:

According to MSDS.

## Relevant information for classification:

\*\*) According to additional method of CLP. For classification, concentrations stated in Section 3 were recalculated according to article 1.1.3.7 of Annex I to CLP.