

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 1 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

SECTION 1: Identification of the mixture and the company/undertaking

1.1 Product identifier:

Trade Name:	MAGICSKIN – PEELABLE MATT BLACK
Mixture description:	Solvent coating (aerosol).
UFI codes:	592P-00EX-H007-3YUD

1.2 Relevant identified uses of the mixture or mixture and uses advised against:

Identified uses:	Paint, surface treatment.
Uses advised against:	Recommended for identified uses.

1.3 Details of the supplier of the safety data sheet:

GOX7-CZECH Service s.r.o.
Chlumčanská 396
439 02 Cítoliby, Czech republic
Tel.:+420 777 691 661
competent person responsible for MSDS: info@gox7.cz

1.4 Emergency telephone number:

112 (General emergency phone).

SECTION 2: Hazards identification

The mixture is classified as **dangerous** as follows:

2.1 Classification of the mixture:


<i>according to 1272/2008/EC</i>	Aerosol 1; H222, H229 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336 Skin Irrit. 2; H315 Aquatic Chronic. 2; H411
----------------------------------	--

Full text of H-phrases: see section 16.

The most important adverse physicochemical, human health and environmental effects:

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2 Label elements:

<i>hazard pictograms</i>	
<i>signal word</i>	Danger.
<i>ingredients of the mixture to be labeled</i>	Contains isopropanol, ethyl-acetate, iso-butanol, naphtha (petroleum), hydrotreated light.
<i>hazard statements</i>	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H315 Causes skin irritation. H411 Toxic to aquatic life with long lasting effects.
<i>precautionary statements</i>	P102 Keep out of reach of children.

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 2 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P403 Store in a well-ventilated place.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P280 Wear protective gloves/protective clothing/eye protection.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
 P501 Dispose of contents/container at the site of hazardous waste collection in the village.

supplemental hazard information VOC 95%.

2.3 Other hazards:

The mixture meets not the criteria for PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

3.2.1 Substances presenting a health or environmental hazard in the mixture

<i>Chemical identity</i>	<i>CAS</i>	<i>EC-No. Registration No.</i>	<i>Content *** (wt. %)</i>	<i>Classification 1272/2008/EC</i>
isopropanol	67-63-0	200-661-7 not available	approx 37	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
petroleum gases, liquefied (LPG) *)	68476-85-7	270-704-2 not available	approx 25	Flam. Gas 1; H220 Press. Gas (Liq.); H280
naphtha (petroleum), hydrotreated light; low boiling point hydrogen treated naphtha **)	64742-49-0	265-151-9 not available	approx 22	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 STOT SE 3; H335 Aquatic Chronic 2; H411
ethyl-acetate	141-78-6	205-500-4 not available	5 - 7	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066
2-methylpropan-1-ol, iso-butanol	78-83-1	201-148-0 not available	4 - 6	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Eye Dam. 1; H318 Skin Irrit. 2; H315
Tinuvin 5060 (mixture (25-75%) CAS 127519-17-9 and 129757-67-1)		not applicable	2-3	Aquatic Chronic 2; H411
2-butoxyethanol; ethylene glycol monobutyl ether	111-76-2	203-905-0 not available	1-2	Acute Tox. 4; H302 +H332; ATEor=1200 Eye Irrit. 2; H319 Skin Irrit. 2; H315
destilates (petroleum), hydrotreated light; **) kerosine - unspecified	64742-47-8	265-149-8 not available	< 0,2	Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411
n-butyl-acetate	123-86-4	204-658-1 not available	< 0.2	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 3 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

4-methylpentan-2-one; methylisobutylketon (MIBK)	108-10-1	203-550-1 not available	< 0,2	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 EUH066
---	----------	----------------------------	-------	---

Contains less than 0.1% of 1,3-butadiene (*); less than 0.1% of benzene (**); *** see section 16 classification procedure.

3.1.2 Impurities, stabilising aditives, constituents other than the main constituent

Chemical identity	CAS	EC-No. Registration No.	Content (wt. %)	Classification 1272/2008/EC
acrylic-polyol resin	does not exist	does not exist not available	< 0,2	does not classified
Carbon Black	1333-86-4	215-609-9 not available	< 0,2	does not classified
amorphous SiO ₂	7631-86-9	231-545-4 not available	< 0,2	does not classified

SECTION 4: First aid measures

Keep the person at physical and mental rest and warm. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

4.1 Description of first aid measures:

Inhalation:

Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. Place unconscious person on the side in the recovery position and ensure breathing can take place.

Skin contact:

Remove contaminated clothing immediately and wash skin with soap and water. Do not use solvents or thinners.

Eye contact:

Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes (least 15 minutes). Get medical attention.

Ingestion:

Unlikely (aerosol). If this nevertheless happens, rinse out mouth with clean water. Do not induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

4.2 Most important symptoms and effects, both acute and delayed:

Overexposure may result in light headedness, staggering gait, dizziness, and possible nausea. May cause skin irritation, eye damage. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system.

4.3 Indication of any immediate medical attention and special treatment needed:

Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing media:

Use water fog, dry chemical, carbon dioxide or foam.

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 4 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

Extinguishing media which shall not be used for safety reasons:

Solid streams of water may be ineffective. Burning product will float on the surface and spread fire.

5.2 Special hazards arising from the substance:

Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapours are heavier than air and may travel along surfaces to remote ignition sources and flash back. Combustion will produce oxides of carbon and hydrocarbons.

5.3 Advice for firefighters:

In the event of fire, wear self-contained breathing apparatus and clothing protective against chemicals. Keep extinguishing aerosols away from the danger area, if possible without risk.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Use non-sparking tools, avoid electrostatic charge. Other protective measures - see section 7.

6.2 Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Do not allow to enter waters or soil. Report spills to authorities as required.

6.3 Methods and material for containment and cleaning up:

Aerosol, mainly local air pollution will occur. If, however, a liquid fraction is leaking, absorb spillage using an absorbent, such as earth, sand or vermiculite. Place in container for disposal according to local regulations (see section 13). Pump off larger quantities. Use non-sparking tools. Afterwards ventilate area and wash spill site.

6.4 Reference to other sections:

Protective equipment: see section 8. Dispose according to the section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Provision of very good ventilation in the working area. Vapour/air mixtures are heavier than air. Adequate ventilation at the floor area must be ensured as well. Eye bath required. These locations must be signposted clearly. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. Keep containers tightly sealed. Prevent formation of aerosols. Do not use any tools that cause sparks.

When using, do not eat, drink or smoke. Wash hands with warm water and soap before breaks and after work.

7.2 Conditions for safe storage, including any incompatibilities:

Store in original tightly closed packing in dry and well-ventilated areas. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature: 5 - 30 °C. Keep away from direct sunlight.

7.3 Specific end use(s):

In household and industry.

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 5 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 Exposure limit value in UK:

LPG:

8 h: 1800 mg/m³ short: 4000 mg/m³

iso-propanol:

8 h: 999 mg/m³, short: 1250 mg/m³

n-butyl-acetate:

8 h: 724 mg/m³, short: 966 mg/m³

2-butoxyethanol:

8 h: 123 mg/m³ short: 246 mg/m³

ethyl-acetate:

8 h: 200 ppm, short: 400 ppm

iso-butanol:

8 h: 154 mg/m³, short: 231 mg/m³

4-methylpentan-2-one:

8 h: 208 mg/m³, short: 416 mg/m³

Carbon Black:

8 h: 3,5 mg/m³, short: 7 mg/m³

8.1.2 DNEL:

DNEL, PNEC are not available.

8.2 Exposure controls

8.2.1 Exposure reduction (technical measures):

Where exposure cannot be prevented by other means the use of individual protection measures, such as personal protection equipment is necessary. Ensure adequate ventilation of the workplace. Regularly measure the concentration of this agent in the workplace atmosphere.

8.2.2 Individual protection measures, such as personal protective equipment:

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier. Workers in the risky process/areas identified should be trained.

Respiratory protection:

Required when vapours/aerosols are generated (recommended filter type A) and where risk assessment shows air-purifying respirators are appropriate use.

Hand protection:

Handle with gloves, e.g. nitril-rubber, strength > 0.55 mm, penetration time > 480 min.; leather is not suitable.

Eye/face protection:

chemical safety goggles

Skin protection:

suitable protective clothing

8.2.3 Environmental exposure reduction:

Uncontrolled escape of substance/formulation into environment is to be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Appearance (at 20 °C):

aerosol

Colour:

by pigment

Odour:

characteristic

Odour threshold:

not available

pH (at 20 °C):

6; 10%

Melting point/freezing point:

not available

Boiling point (range):

not available

Flash point:

< -18 °C (propellant gas)

Flammability:

flammable mixture

Explosive limits

lower: (% vol.)

1,8 (propellant gas)

upper: (% vol.)

12,8 (propellant gas)

Vapour pressure: (20 °C)

not available

Vapour density:

not available

Relative density:

not available

Solubility in water (20 °C) :

not available

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 6 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

Partition coefficient: n-octanol/water:	not available
Auto-ignition temperature:	not available
Decomposition temperature:	not available
Viscosity:	not available
Particle characteristics:	not available
9.2 Other information	
Evaporation rate:	not available
Information with regard to physical hazard classes:	not available
Other information:	not known

SECTION 10: Stability and reactivity

10.1 Reactivity:

Low reactivity.

10.2 Chemical stability:

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions:

Not known.

10.4 Conditions to avoid:

Heat, flames and sparks. Protect from higher temperatures (over 50 ° C) and direct sunlight, risk of aerosol packaging explosion. Do not use in the presence of a source of ignition.

10.5 Incompatible materials:

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon oxides.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

Acute toxicity:	
- LD ₅₀ oral, rat (mg.kg ⁻¹):	ATE _{mixture} > 2000 (2-butoxyethanol LD50 = 1200)
- LD ₅₀ skin, rat or rabbit (mg.kg ⁻¹):	does not contain components so classified
- LC ₅₀ inhalation, rat, gas or vapour (mg.l):	ATE _{mixture} > 20 (MIBK LC50=11,6, for ingredients with LD50 > 20 but classified with H332, ATE is used according to tab. 3.1.2 CLP)
Skin corrosion/irritation:	irritant, cat. 2
Serious eye damage/irritation:	damage, cat. 1
Respiratory or skin sensitisation:	no
Germ cell mutagenicity:	no
Carcinogenicity:	no
Reproductive toxicity:	no
STOT-single exposure:	may cause drowsiness or dizziness, respiratory irritation
STOT-repeated exposure:	based on available data, the classification criteria are not met
Aspiration hazard:	aerosol, not classified
11.2 Information on other hazards:	
Endocrine disrupting properties:	does not contain these substances
Additional information:	not known

SECTION 12: Ecological information

12.1 Toxicity:

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 7 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

- LC ₅₀ 96 H, fish (mg.l ⁻¹):	no data available
- EC ₅₀ 24 H, Daphnia (mg.l ⁻¹):	no data available
- IC ₅₀ 72 H, algae (mg.l ⁻¹):	no data available
12.2 Persistence and degradability:	no data available
12.3 Bioaccumulative potential:	no data available
12.4 Mobility in soil:	no data available
12.5 Results of PBT and vPvB assessment:	product is neither a PBT nor a vPvB substance
12.6 Endocrine disrupting properties:	does not contain these substances
12.7 Other adverse effects:	The mixture is classified as dangerous for the environment according to the additive method, cat. 2.

SECTION 13: Disposal considerations

13.1 Waste treatment methods:

Disposal methods of the substance and the contaminated packaging:

Fully use the aerosol. Do not take the unused product into the collection or other disposal. Do not throw into the fire! Dispose of the packaging after full emptying. Never remove it by draining into drains! The waste producer is responsible for sorting waste and disposing of. Potential EU waste-code 08 01 11 for container, 15 01 10 for mixture.

Physical/chemical properties that may affect waste treatment options:

Highly flammable.

Union provisions relating to waste:

- directive 2008/98/EC

SECTION 14: Transport Information

14.1 UN number:	1950
14.2 UN proper shipping name:	
- ADR/RID/IMDG/IATA	AEROSOLS, flammable
14.3 Transport hazard class(es):	2
14.4 Packing group:	-
14.5 Environmental hazards:	no
14.6 Special precautions for user:	none
14.7 Maritime transport in bulk according to IMO instruments:	not available
ADR/RID:	
- classification code	5F
- labels	2.1
- hazard identification code	-
- tunnel restriction code	D
IMDG:	
- EmS	F-D, S-U

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the mixture:

Regulation No. 1907/2006/ES, REACH.

Regulation No. 1272/2008/ES, CLP.

15.2 Chemical safety assessment:

No data available.

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 8 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

SECTION 16: Other information

Reason for alteration:

28. 03. 2022 - Classification changes of mixture components, changes in Sections 9, 11 and 12.

Key or legend to abbreviations and acronyms used in the safety data sheet:

Flam Gas 1	flammable gas, cat. 1
Press. Gas (liq.)	gas under pressure (liquefied)
Flam. Liq. 3	flammable liquid, cat. 3
Flam. Liq. 2	flammable liquid, cat. 2
Asp. Tox. 1	aspiration toxicity, cat. 1
Aerosol 1	highly flammable aerosol
STOT SE 3	specific target organ toxicity after single exposure, cat. 3
Aquatic Chronic 3	long-term aquatic toxicity, cat. 3
Aquatic Chronic 2	long-term aquatic toxicity, cat. 2
Skin Irrit. 2	irritating for skin, cat. 2
Eye Irrit. 2	irritating for eyes, cat. 2
Eye Dam. 1	damage eyes, cat. 1
Acute Tox. 4	acute toxicity, cat. 4
NOEC	No Observed Effect Concentration
PBT	Persistent, bioaccumulative, toxic chemical
vPvB	Very Persistent and Very Bioaccumulative chemical
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
CLP	regulation No. 1272/2008/EC
REACH	regulation No. 1907/2006/EC
bw	body weight

Sources of key data used to compile the Safety Data Sheet:

Chemical databases and tables, tests.

List of H-phrases:

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H226	Flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H220	Extremely flammable gas.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H302+H332	Harmful if swallowed or if inhaled
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P403	Store in a well-ventilated place.
P211	Do not spray on an open flame or other ignition source.

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 12. 07. 2020

Product code: GX7609

Revision: 28. 03. 2022

Replaced version: 12. 07. 2020

Page: 9 z 9

Trade Name: **MAGICSKIN – PEELABLE MATT BLACK**

P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container at the site of hazardous waste collection in the village.
EUH066	Repeated exposure may cause skin dryness or cracking.

Training advice:

According to MSDS.

Relevant information for classification:

According to additional method of CLP.

***) For classification, concentrations stated in Section 3 were recalculated according to clause 1.1.3.7 of Annex I to CLP.